

Pitot Tubes

Pitot Tubes

Pitot Tube Sample Ports & Accessories

Trico's Pitot Tube sampling ports are designed to provide a safe, simple and effective method of sampling fluids from sumps and non-flooded horizontal drain lines. They ensure oil samples are drawn from the most appropriate location of the sump reservoir, and that the sample is taken from the exact location inside the system each time, which is important for maintaining consistency in routine sampling.

Specifications:

Maximum Pressure	500psi (34.5 bar)
Material	Carbon Steel or Stainless
Check Valve Ball	Stainless Steel
Seal	Viton
Maximum Operating Temp	-4F to-392F

The thick wall tubing can be bended and directed to the ideal sampling location with the use of a swivel adapter.

Carbon Steel Sample Port and Tube (with swivel adapter)

Part Number	Tube Length	Fitting
36217	12"	1/4NPT Male
36220	18"	1/4NPT Male
36223	24"	1/4NPT Male



Sample Port Adapter (Part no. 36133)



Accessories	Part Number
Sample Pump	EAV-38U
Sample Tubing (500 ft.)	FAF-STU500FT
Flush Jar (1 Pint)	SCA-Pint Purge
Replacement Seals (Sample Pump)	EAV-38URK



...because what happens on the inside really counts



9321 - 48 Street
Edmonton, AB T6B 2R4
Phone: (780) 462-2400
Fax: (780) 462-2420
Toll Free: 1-877-962-2400

95 Copernicus Blvd.
Brantford, Ontario N3P 1N4
Phone: (519) 720-9700
Fax: (519) 720-9705

Fluid Life